

Cable Systems · Medium-Voltage

15kV | 单通套管 Bushing insert [®]




Type: ADJ-15/200
(单通套管Bushing insert)

单通套管用于箱变高压引入线，也可用于环网柜高压连接，产品使用时旋紧在套管座上，为肘型插头提供插孔，接触电阻小。

1. Suitable for high voltage incoming line of pad-mounted transformer and ring main unit.
2. Screwed on the bushing to provide a jack for elbow connector.
3. Low contact resistance .

15kV | 双通套管 Bilateral bushing [®]




Type: ADG-15/200
(双通套管Bilateral bushing)

双通套管用于箱变高压引入线，为变压器系统提供过电压保护时安装肘型避雷器使用。也可以将箱变终端接线转变为环网型接线。内部导电结构为一体式铜锻压件，电阻比其它同类焊接式双通套管小 $100\mu\Omega$ 运行时温升更低。独特的限制扭矩结构，确保套管座内螺栓不会被拧断。内置式拔插增力设计，可确保400N的拔插力，使用安全可靠，不会松脱退出引起事故。

1. Suitable for high voltage incoming line of pad-mound transformer.
2. Can mate with elbow connector w/arrester to provide over-voltage protection for transformer system.
3. Has the function to change pad-mounted link into surrounding net link.
4. The inner conductive apparatus is the combination of copper compression.
5. The resistance is $100\mu\Omega$ less than other homogeneous bushings and make the temp. rise very low when operation.
6. Special twist-apparatus make sure no crack will occur on the bolt.
7. The inside increasing force is designed to satisfy 400N swappable force.
8. It is safe, reliable and never get out and bring about.

15kV | 套管座 Bushing wel [®]



Type: ACZ-15/200
(套管座Bushing wel)

套管座用于箱变高压引入线，也可用于环网柜高压连接，产品用压环将其固定于箱体上，座孔内接插单通套管或双通套管。适用于变压器油介质，采用特殊无渗漏结构工艺，具有良好导电性。

1. Suitable for high voltage incoming line of pad-mound transformer and ring main unit.
2. Fixed on the box by steel loop.
3. Can mate with loadbreak busing insert and loadbreak rotatable feed-thru insert.
4. Suitable for transformer oil dielectric.
5. Adopted special non-leakage technology, has good conductive performance.

