

35kV | 后接避雷器 Rear connector w/arrester



Type: AHY5WZ-51/134
(后接避雷器 Connector w/arrester)

插头避雷器性能参数

Performance parameter of connector w/arrester

额定电压51kV

Rated voltage 51kV

持续运行电压40.8kV

Continuous operation voltage 40.8kV

5kA雷电冲击电流下残压134kV

5kA lightning impulse current residual voltage 134kV

直流1mA下电压 $U_{1mA} \geq 73kV$

At D.C. 1mA voltage (U_{1mA}) $\geq 73kV$

0.75 U_{1mA} 直流漏电流 $\leq 50 \mu A$

Leaking current at D.C. 0.75 $U_{1mA} \leq 50 \mu A$

2ms方波冲击容量400A

2ms rectangular current withstand 400A

- 1、电缆 Cable
- 2、应力锥 Cable adaptor
- 3、接地线 Earthing wire
- 4、前接头 Front connector body
- 5、套管 Bushing
- 6、封帽 Screen cover
- 7、绝缘塞 Insulating plug
- 8、双头螺栓 Bolt
- 9、铜连接杆 Copper linking rod
- 10、圆头端子 Compression lug
- 11、后接头 Rear connector body
- 12、半导电层 Semi-conductive layer

